

# Defoamer 6237-D10

## Metal Working Coolant Defoamer

### DESCRIPTION

**Defoamer 6237-D10** is a water miscible defoamer. It has shown outstanding efficiency as a defoamer for coolants in industrial applications.

### HOW TO USE

The recommended addition rate for **Defoamer 6237-10** is generally in the order of 10 to 20 ml per 100 litres (0.01% - 0.02%) of the coolant emulsion. This may be customised to suit individual needs or solutions, which may vary from time to time. Houghton strongly advises that you contact your Sales Representative to discuss before commencement of use.

**Defoamer 6237-D10** Should Be Shaken Vigorously before use, add directly to coolant system where good agitation occurs.

### SHELFLIFE & AVAILABIL-

Under normal conditions the recommended shelf life for **Defoamer 6237-D10** is a minimum of Twelve (12) months, unless otherwise specified.

**Defoamer 6237-D10** is available in 5 litre and 20 litre packs.

### HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

### TYPICAL VALUES

Appearance	Opaque, Off White Liquid
Solubility in Water	Yes



Houghton Australia Pty Ltd  
287 Wickham Road  
Moorabbin VIC 3189 Australia

Phone: +61 1300 736 642  
Fax: +61 1300 736 234  
Sales.au@houghtonintl.com  
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.