

HONING OIL MM

Metal Honing Compound

DESCRIPTION

Houghton's HONING OIL MM is a low viscosity, dark coloured liquid. It is essentially a blended lubricant made up of petroleum hydrocarbons and fatty oils, and treated with sulphur to give it extreme pressure characteristics. This product is carefully compounded to assure long stone life, fast stock removal and superior finish.

HONING OIL MM is used straight for honing operations on hard steels. For softer stock steels and hard bronzes, it may be diluted with up to 3 parts of light oil.

FEATURES

- Low coefficient of friction
- Eliminates scoring
- Easily applied

TYPICAL VALUES

Viscosity @40C	10 cSt
Density @150C	0.870 kg/L
Flash Point (Open Cup)	900C
Chlorine content	0%
Sulphur content	2.5%
Saponifiable content	33%

SHELF LIFE & AVAILABILITY

Under normal conditions the recommended shelf life for **PRODUCT** is a minimum of Twelve (12) months, unless otherwise specified.

PRODUCT is available in 205 litre drums. Other sizes may be available upon request, please contact your Houghton sales representative.

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.



Houghton Australia Pty Ltd
287 Wickham Road
Moorabbin VIC 3189 Australia

Phone: +61 1300 736 642
Fax: +61 1300 736 234
Sales.au@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.