HOUGHTO-GRIND 03A

Grinding Oil for Superior Finish

DESCRIPTION

HOUGHTO - GRIND 03A is a special adaptation of highly effective grinding oil used extensively throughout Europe. The combination of lubricity agents, an effective inhibitor package, anti misting agents and single cut base oil make it an ideal multi-application fluid.

High production to dressing ratios can be expected as a norm while using HOUGHTO-GRIND 03A. Low surface roughness and full surface integrity is to be expected. To maintain surface quality, HOUGHTO-GRIND 03A can be filtered without altering product chemistry or efficacy.

FEATURES

- Excellent Surface Finish
- · Light Viscosity Light Coloured
- Minimises Built Up Edge at Cutting Tip
- Can be use also on non-ferrous Alloys

HOW TO USE

Use product as received.

SHELFLIFE & AVAILABILITY

Under normal conditions the recommended shelf life for **PRODUCT** is a minimum of Twelve (12) months, unless otherwise specified.

PRODUCT is available in 205 litre drums. Other sizes may be available upon request, please contact your Houghton sales representative.

TYPICAL VALUES

Appearance Pale Amber Liquid

Density @15°C 0.845 kg/L

Viscosity @40°C 8-10 cSt

Flash Point (Close Cup) >150°C

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.



Houghton Australia Pty Ltd 287 Wickham Road Moorabbin VIC 3189 Australia Phone: +61 1300 736 642 Fax: +61 1300 736 234 Sales.au@houghtonintl.com www.houghtonintl.com