

# CINDOL® 869R

## Vegetable Oil Based Lubricant

### DESCRIPTION

CINDOL 869R was developed specifically as a high performance lubricant for Aluminium machining and forming.

Due to its vegetable oil base, **CINDOL 869R** is ideal for use in metal working operations where biodegradability and operator health and safety are of prime importance. Use as supplied in place of petroleum based fluids.

CINDOL 869R can also be used for forming, machining, drawing and blanking on most ferrous and nonferrous metals. CINDOL 869R is suitable for application by swab, spray mist and flood.

### TYPICAL VALUES

Appearance	Clear liquid
Odour	Bland
Density @15°C	0.920 kg/L
Viscosity @40°C	35 cSt
Flash Point (Close Cup)	>200°C

### HOW TO USE

**CINDOL 869R** is used neat as supplied.

### FEATURES

- Environmentally friendly
- Biodegradable 100%
- User friendly
- Low odour
- Excellent lubricity
- Cost effective

### SHELF LIFE & AVAILABILITY

Under normal conditions the recommended shelf life for **CINDOL 869R** is a minimum of Twelve (12) months, unless otherwise specified.

**CINDOL 869R** available in 205 litre drums. Other sizes may be available upon request, please contact your Houghton sales representative.

### HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

01 July 2011 Version 1.0, Code: D001A0200



Houghton Australia Pty Ltd  
287 Wickham Road  
Moorabbin VIC 3189 Australia

Phone: +61 1300 736 642  
Fax: +61 1300 736 234  
sales.au@houghtonintl.com  
www.houghtonintl.com

This document contains information based on data that is believed to be correct.