

Rust Veto® 377DGHF

Raises Water off Wet Metal to Prevent Rust with a Very Thin Film

DESCRIPTION

Polar-type, water displacing Rust Veto 377DGHF actually raises water off wet metal to coat the entire metal surface with an economical, long-lasting film. It slides under the most microscopic drops of water to spread a thin film of rust preventive.

Rust Veto 377DGHF is a real multi-purpose product. Use it across the board for indoor protection of critical surfaces or for packaged materials. Examples are hardware, ball bearings, dies, tools, fixtures, gauges, polished steel, phosphatised surfaces and idle or stored machinery.

HOW TO USE

Rust Veto 377DGHF is used neat. It can be used in spray applicators and most commonly used in various dip applications.

SHELF LIFE & AVAILABILITY

Under normal conditions the recommended shelf life for **Rust Veto 377 DGHF** is a minimum of Twelve (12) months, unless otherwise specified.

Rust Veto 377 DGHF is available in 205 litre drums. Other sizes may be available upon request, please contact your Houghton sales representative.

TYPICAL VALUES

Appearance Light yellow thin film

Film Character Soft

Flash Point 90°C

Density @15°C 0.850 kg/L

Withstands 100% humidity @ 40°C for more than 30 days

Indoor Protection - unwrapped 18-24 months

Shed Protection 4-6 months

Rust Veto 377 DGHF is used in the manufacture of Steel

FEATURES

- Displaces water
- Excellent coverage reduces cost
- Compatible with lubricants
- Easy to remove
- High flash point
- Use with wet metal Metal doesn't need to be completely dry when Rust Veto 377DGHF is applied.
- Economical Fine film and attraction for metal make Rust Veto 377DGHF "creep" across the metal's surface, spreading over a large area.
- Ideal for bi-metals Can be used safely with many combinations of ferrous or non-ferrous metals and alloys with no reaction.
- Long-lasting film Rust Veto 377DGHF has an anti-oxidant additive. It won't break down and corrode metal. Resists oxidation even under long-term storage. Its affinity for metal means the film adheres to the surface, handling won't wipe the film off.

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.



Houghton Australia Pty Ltd
287 Wickham Road
Moorabbin VIC 3189 Australia

Phone: +61 1300 736 642
Fax: +61 1300 736 234
Sales.au@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.