

SEF 2

Spark Eroding

DESCRIPTION

SEF 2 is specifically designed for use as a dielectric fluid in electrical discharge machining (EDM) used in the metal working industry for manufacturing of dies and moulds where complex shapes and close tolerances are required.

SHELFLIFE & AVAILABILITY

Under normal conditions the recommended shelf life for **PRODUCT** is a minimum of Twelve (12) months, unless otherwise specified.

PRODUCT is available in 205 litre drums. Other sizes may be available upon request, please contact your Houghton sales representative.

TYPICAL VALUES

Appearance	Clear
Colour	Water white
Odour	Bland
Viscosity @40C	2.5 cSt
Flash Point	>1050C
Density @150C	0.810 kg/L

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

01 July 2011 Version 1.0, Code: D001A0200



Houghton Australia Pty Ltd
287 Wickham Road
Moorabbin VIC 3189 Australia

Phone: +61 1300 736 642
Fax: +61 1300 736 234
Sales.au@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.